

## 14cm Built-In Warming Drawer

22L Capacity with 9 Temperature Settings and Digital Touch Control





### **PRODUCT FEATURES**

#### **22 LITRE CAPACITY**

With a 22 litre capacity, you can load up to 6 place settings to pre-heat dinnerware before serving, or up to 80 espresso cups for an ultimate café experience at home.

#### **FOOD WARMING & DEFROST**

With a dedicated 'Keep Warm' function, you can place your completed dishes inside to maintain a safe serving temperature while you finish preparing your meal. This feature can also be used on a lower temperature to rapidly defrost frozen food.

#### **SLOW COOKING**

Food can be cooked to a core temperature of up to 70°C in the warming drawer. This feature is particularly suitable for large, tender pieces of meat to maintain flavour and juiciness while cooking.

#### SOFT-CLOSING DRAWER

The warming drawer is fitted with a soft-closing mechanism, enabling the door to close gently with an effortless motion and prevents the door from slamming shut.

#### **MULTI-TEMP CONTROL & DIGITAL TIMER**

With up to 9 temperature settings ranging from 40-80°C, as well as a timer to set your heating duration, you can easily select your preferred settings using the digital touch control interface.

#### **BELLING FAMILY**

Matching finishes to the Belling Design Collection range provides a high-end, stylish look to any kitchen.

### **BDWDBK**

Under-bench or wall unit

10A Plug & Lead 220 - 240V, 50 / 60Hz

> 600W 1000W

705 (w) x 210 (h) x 640 (d)

20.5

595 (w) x 141 (h) x 541 (d)


18


598 (w) x 141 (h) x 550min (d)





# Specifications, Dimensions and Installation

55<sup>4</sup> 141 695 141 SA1 2









| FUNCTIONS                  |                              | INSTALLATION / CONNECTION   |
|----------------------------|------------------------------|-----------------------------|
| Food Warming               | Yes                          | Installation type           |
| Low Temperature Cooking    | Yes                          | Electrical connection       |
| Defrosting                 | Yes                          | Rated voltage               |
| Cups & Glasses Warming     | Yes                          | Heating Output              |
| Plates & Dishes Warming    | Yes                          | Total Rated Power           |
| Cookware & Utensil Warming | Yes                          | DIMENSIONS (PACKED)         |
| Dough Proving              | Yes                          | Width x Height x Depth (mm) |
| Sterilising                | Yes                          | Gross weight (kg)           |
| CONTROL PANEL              |                              | DIMENSIONS (PRODUCT)        |
| Clock / Timer              | Digital Timer                | Width x Height x Depth (mm) |
| Control type               | Touch control                | Gross weight (kg)           |
| Temperature Control        | Yes                          |                             |
| Start / Pause              | Yes                          | DIMENSIONS (CUT-OUT)        |
| PRODUCT FEATURES           |                              | Width x Height x Depth (mm) |
| Actual capacity (litres)   | 22L                          |                             |
| Cavity finish              | Stainless steel              |                             |
| Cavity Dimensions (mm)     | 97.2 (h) x 540 (w) x 420 (d) |                             |
| Temperature Settings       | 9                            |                             |
| Temperature Range          | 40°C - 80°C                  |                             |
| Max. Place Settings        | 6                            |                             |
| Max. Dinner Plates (26cm)  | 12                           |                             |
| Max. Espresso Cups         | 80                           |                             |
| Max. Weight Capacity       | 25kg                         |                             |
| Push-Open                  | Yes                          |                             |
| Soft-Closing Mechanism     | Yes                          |                             |
|                            |                              |                             |

Connection cable L = 1000 mm 19.5

(1) Ventilation cut-out required when combined with a pyrolytic oven <sup>(2)</sup> Building-in dimension including mains supply cable connection