

# CookCentre Deluxe 110cm Induction Range Cooker



### The CookCentre Deluxe with Quad Oven

Giving you 4 independent ovens in the one range cooker













#### Colours





Black: BCC1100IB | Stainless Steel: BCC1100ISS

### **Features & Benefits**



### **Huge 224L Capacity**

Maximum capacity, endless results. Creating as much space as possible, our combined 224L capacity ovens give you the versatility of cooking the largest roast and baking desserts for the masses all at once.



### Oven 1: 41L Compact Oven with Grill

Perfect for efficiently cooking small meals, the small oven combines a conventional oven with a multi-function grill.



#### Oven 2: 71L Multi-function Oven for Perfect Results

With 13 settings to choose from such as Fan and Conventional options, Pizza function, Grill settings and more, you can perfectly cook anything from pavlova to pastizzi with ease.



#### Oven 3: 71L Equiflow™ Oven

Features 5 essential settings: Equiflow<sup>™</sup> Fan Forced Cooking, Slow Cook, Keep Warm, Bread Proving and Light.



#### Oven 4: 41L Slow Cook Oven

A dedicated Slow Cook Oven perfect for using your favourite cast iron dish to cook tender and tasty slow cooked meals. Also ideal to use as a plate warmer.



#### **Induction Cooktop**

5 zone induction hotplate with EuroKera glass and a digital display. Touch slide controls and 10 power levels including boost. Induction features include Timer, Child Safety Lock, Pan Detection, Overheat Pan Detection, Individual Residual Heat Indicators and preset functions.



#### **Additional Features**

Includes removable double extending telescopic runners, a large easy to read white LED display and touch control screen, full width oven pans, premium knobs and rear wheels.

## **Functions**

## Top Left

### **Top Right**



















**Bottom Right** 

**Bottom Left** 



























## **COOKCENTRE DELUXE BCC11001**

COOKTOP	
No. of elements	5
Fuel	Electric
INDUCTION COOKTOP	
Element 1 (kW)	Medium (1.6 - 3.0 Boost)
Element 2 (kW)	Medium (1.6 - 3.0 Boost)
Element 3 (kW)	Large (2.3 - 3.7 Boost)
Element 4 (kW)	Small (1.1 - 2.2 Boost)
Element 5 (kW)	Medium (1.4 - 3.0 Boost)
Central on/off key	Yes
Individual residual heat indicators	Yes
CAVITY 1	
Position	Top left
Function	Conventional oven and grill
ELECTRIC OVEN / GRILL	
Variable rate dual circuit electric grill	Yes
Conventional electric oven	Yes
CAVITY 1 FEATURES	
Oven capacity (litres)	41 (Gross) / 35 (Net)
Internal dimensions (mm)	470 (w) x 180 (h) x 430 (d)
Power (kW)	Oven (1.4) & Grill (1.7/2.7)
No. of shelves	1
No. of shelf positions	2
Full width oven pans with reversible trivet	1
Door opening	Drop-down
CAVITY 2	
Position	Bottom left
Function	Multi-function oven
ELECTRIC OVEN	
Variable rate electric grill	Yes
Conventional electric oven	Yes
Fanned electric oven	Yes
Defrost	Yes
Intensive bake (top, bottom & fan)	Yes
Top heat only	Yes
Base heat only	Yes
Base heat with fan	Yes
Grill with fan	Yes
Slow cook	Yes
Pizza	Yes
Keep warm	Yes

CAVITY 2 FEATURES  Oven capacity (litres)  Internal dimensions (mm)  Power (kW)  No. of shelves  2  No. of shelf positions  Full width oven pans with reversible trivet  Telescopic shelves  Oven light  Programmable timer  Door opening  CAVITY 3  Position  Function  ELECTRIC OVEN  Fanned electric oven  Slow cook  Keep warm  Power (kW)  No. of shelf positions  Top right  Fan forced oven  ELECTRIC OVEN  Fanned electric oven  Slow cook  Keep warm  Power (kW)  No. of shelf positions  Oven Light  Door opening  CAVITY 3 FEATURES  Oven capacity (litres)  Internal dimensions (mm)  Power (kW)  Position  Function  Electric  CAVITY 4 FEATURES  Oven capacity (litres)  Internal dimensions  Oven Light  Position  Bottom right  Slow cook oven  Electric  CAVITY 4 FEATURES  Oven capacity (litres)  Internal dimensions  Oven Light  Position  Function  Power (kW)  O.17  Door opening  Timer  Minute minder  Key lock feature  INSTALLATION  Minimum gap required to fit appliance (mm)  Power supply  Total electrical power load (kW)  DIMENSIONS (PRODUCT)  Height x Width x Depth (mm)  Pour 2,00 (Net)  1106 (10mm clearance each side)  Pover supply  240V / 415V single phase / 3 phase  15.525		
Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Poor opening CAVITY 3 Position Function Fanned electric oven Slow cook Keep warm Pread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Poor opening CAVITY 4 Position Function Function CAVITY 4 Position Function Function Power (kW) Poor opening CAVITY 4 Position Function Funct	CAVITY 2 FEATURES	
Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Poor opening CAVITY 3 Position Function Fanned electric oven Slow cook Keep warm Pread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Poor opening CAVITY 4 Position Function Function CAVITY 4 Position Function Function Power (kW) Poor opening CAVITY 4 Position Function Funct		71 (Gross) / 60 (Net)
Power (kW) No. of shelves No. of shelves No. of shelf positions Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Slow cook Keep warm Sraad proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Fention Bottom right Function Functio	Internal dimensions (mm)	470 (w) x 325 (h) 395 (d)
No. of shelves No. of shelf positions Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Function Bottom right Function Function Function Function Function Function Fan forced oven Function Functio	Power (kW)	
Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Electric COVEN Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Functi	, , ,	
Full width oven pans with reversible trivet Telescopic shelves Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Electric COVEN Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Functi	No. of shelf positions	6
Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Yes Pres GAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening CAVITY 4 Position Function Functio	Full width oven pans with reversible trivet	1
Oven light Programmable timer Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Press Press Oven capacity (litres) No. of shelfves Door opening CAVITY 4 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Feep warm Press Oven capacity (litres) Internal dimensions (mm) Power (kW) Power (kW) Door opening CAVITY 4 Position Function Fun	Telescopic shelves	1 double extending, removable
Door opening CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves Door opening CAVITY 4 Position Function Funct	Oven light	Yes
CAVITY 3 Position Function ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves CAVITY 4 Position Function Func	Programmable timer	Yes
Position Function  ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Tyes  Yes Yes  Yes  Total electrical power load (kW) DIMENSIONS (PRODUCT)	Door opening	Side opening
Function  ELECTRIC OVEN  Fanned electric oven  Slow cook  Keep warm  Bread proving  CAVITY 3 FEATURES  Oven capacity (litres) Internal dimensions (mm)  Power (kW)  No. of shelves  No. of shelf positions  Oven Light  Door opening  CAVITY 4  Position  Function  Functi	CAVITY 3	
ELECTRIC OVEN Fanned electric oven Slow cook Keep warm Yes Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Oner (kW) Toor opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Yes Yes Yes Yes  Yes  Yes  Yes  Yes	Position	Top right
Fanned electric oven Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves Door opening CAVITY 4 Position Function Funct	Function	Fan forced oven
Slow cook Keep warm Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW)  Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)	ELECTRIC OVEN	
Yes	Fanned electric oven	Yes
Bread proving CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW)  Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  71 (Gross) / 60 (Net) Side opening Side opening Electric Cavity 4 FEATURES Oven capacity (litres) 71 (Gross) / 60 (Net) 17 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 11 (Gross) / 60 (Net) 12 (Gross) / 60 (Net) 13 (Gross) / 60 (Net) 14 (Gross) / 60 (Net) 15 (Gross) / 60 (Net) 16 (Gross) / 60 (Net) 17 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 10 (Gross) / 60 (Net) 11 (Gross) / 60 (Net) 12 (Gross) / 60 (Net) 13 (Gross) / 60 (Net) 14 (Gross) / 60 (Net) 15 (Gross) / 60 (Net) 16 (Gross) / 60 (Net) 17 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 18 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 19 (Gross) / 60 (Net) 10 (Gross) / 60 (Net) 11 (Gross) / 60	Slow cook	Yes
CAVITY 3 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) On capacity (litres) Internal dimensions (mm) Power (kW) Toor opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  71 (Gross) / 60 (Net) 17 (Gross) / 60 (Net) 18 (100 (Net) 19 (100 (Net) 110 (100 (Net) 15.525	Keep warm	Yes
Oven capacity (litres) Internal dimensions (mm) Power (kW) No. of shelves No. of shelf positions Oven Light Position Power in With the positions Oven Light Position Solve opening CAVITY 4 Position Function Function Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  71 (Gross) / 60 (Net) 170	Bread proving	Yes
Internal dimensions (mm)	CAVITY 3 FEATURES	
Power (kW)   2.0   2   No. of shelves   2   No. of shelves   2   No. of shelf positions   6   Oven Light   Yes   Side opening   Side opening   CAVITY 4   Position   Bottom right   Slow cook oven   Electric   CAVITY 4 FEATURES   Oven capacity (litres)   Total dimensions (mm)   470 (w) x 350 (h) 395 (d)   Over kW)   Door opening   Drop-down   TIMER   Minute minder   Yes   Yes   NSTALLATION   Minimum gap required to fit appliance (mm)   1106 (10mm clearance each side)   Power supply   Total electrical power load (kW)   DIMENSIONS (PRODUCT)   15.525   Total electrical power load (kW)   DIMENSIONS (PRODUCT)   Drop-down   Tiscopies   Total electrical power load (kW)   DIMENSIONS (PRODUCT)   15.525   Total electrical power load (kW)   DIMENSIONS (PRODUCT)   Total electrical power load (kW)   Total electrical power	Oven capacity (litres)	71 (Gross) / 60 (Net)
No. of shelves   2	Internal dimensions (mm)	470 (w) x 350 (h) 395 (d)
No. of shelf positions Oven Light Door opening CAVITY 4 Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Side opening Bottom right Slow cook oven Electric (Gross) / 60 (Net) 470 (w) x 350 (h) 395 (d) 0.17 Drop-down 170P-down 170P-d	Power (kW)	2.0
Oven Light Door opening CAVITY 4 Position Function Slow cook oven Electric  CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power lock Minute minder wes lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power lock DIMENSIONS (PRODUCT)  Yes  1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525	No. of shelves	2
Door opening CAVITY 4 Position Function Function Slow cook oven Electric  CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Bottom right Electric F1 (Gross) / 60 (Net) A70 (w) x 350 (h) 395 (d) D.17 Drop-down F2 F2 F3 F4 F4 F5 F5 F6 F6 F7		
CAVITY 4 Position  Function  Fuel  CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Bottom right Slow cook oven Electric  71 (Gross) / 60 (Net) 470 (w) x 350 (h) 395 (d) 0.17 Drop-down  470 (w) x 350 (h) 395 (d) 0.17 Drop-down  1106 (nom clearance each side) 2400 / 415V single phase / 3 phase		Yes
Position Function Fuel CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Block occord oven Flectric  ATO (w) x 350 (h) 395 (d) D17 Drop-down D17 Drop-down Pres Yes Yes Yes 1106 (10mm clearance each side) 1106 (10mm clearance each side) 15.525	, 0	Side opening
Function Fuel  CAVITY 4 FEATURES Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Slow cook oven Electric 171 (Gross) / 60 (Net) 170 (Net) 170 (Pross) / 60 (Net		
Fuel Electric  CAVITY 4 FEATURES  Oven capacity (litres) 7.1 (Gross) / 60 (Net) Internal dimensions (mm) 470 (w) x 350 (h) 395 (d)  Power (kW) 0.17  Door opening Drop-down  TIMER  Minute minder Yes  Key lock feature Yes INSTALLATION Minimum gap required to fit appliance (mm) Power supply  Total electrical power load (kW) DIMENSIONS (PRODUCT)		
CAVITY 4 FEATURES  Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  71 (Gross) / 60 (Net) Drop-down 470 (w) x 350 (h) 395 (d) Drop-down 470 (w) x 350 (h) 395 (d) Foyer (kW) x 350 (		
Oven capacity (litres) Internal dimensions (mm) Power (kW) Door opening TIMER Minute minder Key lock feature IINSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  71 (Gross) / 60 (Net) 470 (w) x 350 (h) 395 (d) 0.17 Drop-down Yes Yes Yes 1106 (10mm clearance each side) 2400 / 415V single phase / 3 phase		Electric
Internal dimensions (mm)  Power (kW)  Door opening  TIMER  Minute minder  Key lock feature  INSTALLATION  Minimum gap required to fit appliance (mm)  Power supply  Total electrical power load (kW)  DIMENSIONS (PRODUCT)  470 (w) x 350 (h) 395 (d)  0.17  Drop-down  Yes  Yes  Yes  1106 (10mm clearance each side)  2400 / 415V single phase / 3 phase  15.525		
Power (kW) Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  0.17 Drop-down Yes Yes Yes 1106 (10mm clearance each side) 240V / 415V single phase / 3 phase	1 , 1	
Door opening TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Drop-down  Yes  Yes  1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525	, ,	
TIMER Minute minder Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Yes Yes 1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525	, ,	
Minute minder  Key lock feature  INSTALLATION  Minimum gap required to fit appliance (mm)  Power supply  Total electrical power load (kW)  DIMENSIONS (PRODUCT)  Yes  1106 (10mm clearance each side)  240V / 415V single phase / 3 phase  15.525		Drop-down
Key lock feature INSTALLATION Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  Yes  1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525		Vac
INSTALLATION  Minimum gap required to fit appliance (mm)  Power supply  Total electrical power load (kW)  DIMENSIONS (PRODUCT)  1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525		
Minimum gap required to fit appliance (mm) Power supply Total electrical power load (kW) DIMENSIONS (PRODUCT)  1106 (10mm clearance each side) 240V / 415V single phase / 3 phase 15.525	*	103
Power supply 240V / 415V single phase / 3 phase Total electrical power load (kW) 15.525 DIMENSIONS (PRODUCT)		1106 (10mm clearance each side)
Total electrical power load (kW) 15.525  DIMENSIONS (PRODUCT)		
DIMENSIONS (PRODUCT)	,	
	. , ,	10.020
300 300 X 1000 X 000		900 - 930 x 1096 x 600

If this appliance is installed near vinyl wrapped surfaces, we strongly recommend using an installation kit available from the vinyl-wrap supplier. Belling cannot accept any responsibility for damage caused due to installation into cabinets with low temperature tolerances.

Additional accessories available - please see belling.com.au for more information